

ALUPLEX ONBEHANDELD – FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
40 mm	215	95
	235	95
	235	110
	250	122
	300	125
54 mm	215	95
	235	95
	235	110
	250	122
	300	125

ALUPLEX MDO (WIT) – FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
40 mm	215	95
	235	95
	235	110
	250	122
54 mm	215	95
	235	95
	235	110
	250	122

AluPlex op bestelling:

ALUPLEX ONBEHANDELD – FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
66 mm	215	95
	235	95
	235	110
	250	122

ALUPLEX MDO (WIT) – FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
66 mm	215	95
	235	95
	235	110
	250	122



ALUTHERM ONBEHANDELD – FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
40 mm	215	95
	235	95
	235	110
	250	122
	300	125
54 mm	215	95
	235	95
	235	110
	250	122

ALUTHERM MDO (WIT) - FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
40 mm	215	95
	235	95
	235	110
	250	122
54 mm	215	95
	235	95
	235	110
	250	122

AluTherm op bestelling:

ALUTHERM ONBEHANDELD - FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE
54 mm	300	125



ALUCOYA ONBEHANDELD - FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE	DORPEL
54 mm	215	95	15 cm
	235	95	15 cm
	242	95	15 cm
	235	110	15 cm
	242	120	15 cm

AluCoya op bestelling:

ALUCOYA ONBEHANDELD – FSC® gecertificeerd

DIKTE	LENGTE	BREEDTE	DORPEL
40 mm	215	95	10-15 cm
	235	95	10-15 cm
	242	95	10-15 cm
	235	110	10-15 cm
	242	120	10-15 cm
	295	120	10-15 cm
54 mm	215	95	10-15 cm
	235	95	10-15 cm
	242	95	10-15 cm
	235	110	10-15 cm
	242	120	10-15 cm
	295	120	10-15 cm